



- NOTES: (b)**
1. METAL SHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
  2. INSULATORS: PBT GF UL 94 V-0; BLACK
  3. CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL
  4. METAL BRACKETS: ZINC DIE CAST; 300µm COPPER/40-120µm NICKEL/120-200µm TIN
  5. THREADED LOCKS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
  6. FIXING-PLATE: PBT GF UL 94 V-0; BLACK
  7. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
  8. CONNECTOR IS PART MARKED: **163A16529X CONECC ABC**

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: SEE NOTES	
	date	name	title:			
	drawn 24.03.2004	Mankopf	<b>D-SUB MALE 90°</b> 15pos. SOLDER PIN ANGLED 0.318inch threaded lock and metal bracket			
	appd. 24.03.2004	Mickenbecker				
norm		dwg no:		DIN-A3		
d-old		16K1A1129		sh: 2/6		
3 x b	A4036	07.07.2011	K.H.	part no: 163A16529X		
a	Original					
rev.	description	date	name	<b>CONEC</b>		