



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; BLACK
3. HIGH POWER CONTACTS 10A: COPPER ALLOY
PLATING MATING AREA: GOLD FLASH over NICKEL
PLATING TERMINATION SIDE: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 16-20
FEMALE CONTACT ON POS. A1; MALE CONTACT ON POS. A2
4. CAPACITANCE: 47nF ± 20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 2F2CPA22S41A10X CONEC ABC

SOLDER INSTRUCTION:

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350°C
3. SOLDER TIME max. 15s

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: SEE NOTES	
			date		title:	
			name		D-SUB FILTER COMBINATION MALE	
			drawn 27.08.12 Henneboel		2W2CP SOLDER CUP	
			appd. 27.08.12 Fischer			
		norm		dwg no:		
		d-old		24K1A1405		
a Original				DIN-A3		
rev. description date name				sh: 1		
				part no: 2F2CPA22S41A10X		