



**SOLDER INSTRUCTION:**

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350 °C
3. SOLDER TIME max. 15s

**NOTES:**

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: PBT GF UL 94 V-0, BLACK
3. HIGH POWER CONTACTS 10A: COPPER ALLOY  
PLATING MATING AREA: GOLD FLASH over NICKEL  
PLATING TERMINATION SIDE: GOLD FLASH over NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 16-20  
MALE CONTACT ON POS. A1 and A3, FEMALE CONTACT ON POS. A2
4. CAPACITANCE: 12 nF ± 20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 3F3CPA14S41A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)		
				material: SEE NOTES		
	drawn	05.01.12	name		title: <b>D-SUB FILTER COMBINATION MALE          3F3CP SOLDER CUP</b>	
	appd.	31.01.12	Fischer			
	norm					
	d-old				dwg no: 24K1A1358	
a	Original			DIN-A3 sh: 1		
rev.	description			part no: 3F3CPA14S41A10X		