



**SOLDER INSTRUCTION:**

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350°C
3. SOLDER TIME max. 15s

**NOTES:**

1. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATOR: PBT GF UL 94 V-0, BLACK
3. HIGH POWER CONTACTS 10A: COPPER ALLOY  
PLATING MATING AREA: GOLD FLASH over NICKEL  
PLATING TERMINATION SIDE: GOLD FLASH over NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 16-20  
MALE CONTACT ON POS. A2, FEMALE CONTACTS ON POS. A1 and A3
4. CAPACITANCE: 12nF ± 20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 3F3CSA14S41A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance	dim. in mm	scale:	2:1 (5:1)		
					date		name	material:	SEE NOTES	
					drawn	29.11.11	Henneboel	title: <b>D-SUB FILTER COMBINATION FEMALE          3F3CS SOLDER CUP</b>		
					appd.	29.11.11	Fischer			
					norm					
					d-old			dwg no:		
				rev.	a	Original	24K1A1352		DIN-A3	
				description	date	name	part no:		3F3CSA14S41A10X	
				<b>CONEC</b> ®			sh: 1			