



**NOTES:**

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. HIGH POWER CONTACTS 20A: COPPER ALLOY  
PLATING MATING AREA: GOLD FLASH over NICKEL  
PLATING TERMINATION SIDE: GOLD FLASH over NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 12-14
4. CAPACITANCE: 47nF ±20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 3F3SSC22S42A10X CONEC ABC

**SOLDER INSTRUCTION:**

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350°C
3. SOLDER TIME max. 15s

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND			tolerance	dim. in mm	scale: 2:1 (5:1)	
			date		name	material: SEE NOTES
			drawn	23.05.13	Henneboel	title: <b>D-SUB FILTER COMB. FEMALE</b> 3W3SS SOLDER CUP
			appd.	23.05.13	Fischer	
			norm			
			d-old			dwg no:
a	Original				24K1A1444	DIN-A3 sh: 1
rev.	description	date	name	<b>CONEC</b> ®		part no: 3F3SSA22S42A10X