



NOTES:

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0, BLACK
- FRAME: STEEL; NICKEL PLATED
- FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
- RIVETED INSERTS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- CONNECTOR WILL BE SUPPLIED WITHOUT CONTACTS
- CONNECTOR IS PART MARKED: **DSS3XPXXB01X CONEC ABC**

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)		
				material: SEE NOTES		
	drawn	17.01.14	Lehmenkühler	title: D-SUB MALE 25pos. CRIMP STYLE with frame and float mount		
	appd.	17.01.14	Koch			
norm						
d-old			dwg no:		DIN-A3	
a	Original		16K1A3380		sh: 1	
rev.	description	date	part no: DSS3XPXXB01X			

CONEC