

used for: RJ 45

P.C.B. HOLE DRILLINGS

NOTES:

1. HOUSING MATERIAL: GLASS FILLED POLYESTER, BLACK
2. SHIELD MATERIAL: 0.2mm THICK COPPER ALLOY
3. CONTACT MATERIAL: 0.35mm THICK COPPER ALLOY
4. MATING AREA PLATING: min. 50µin GOLD over min. 30µin NICKEL
5. SOLDER TAILS PLATING: min. 90µin TIN/LEAD over min. 30µin NICKEL
6. LED: GREEN AND YELLOW
7. INTERNAL CIRCUIT PER PORT SEE 39K1A041

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
a	Original		

tolerance		dim. in mm	
2012	date	name	
drawn	12.03.	Henneboel	
appd.	13.03.	Koch	
norm			
d-old			

scale:	2:1
material:	SEE NOTES
title:	RJ 45 MAGNETIC MODULAR JACK 2. PORT SOLDER PIN STRAIGHT fully screened, with LED
dwg no:	39K1A615
part no:	RJ45TJS21AC010X

DIN-A
3
sh: 1/1