



SOLDER INSTRUCTION:

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350 °C
3. SOLDER TIME max. 15s

NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; BLACK
3. HIGH POWER CONTACTS 40A: COPPER ALLOY
PLATING, MATING AREA: GOLD FLASH over NICKEL
PLATING, TERMINATION SIDE: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 8-10
FEMALE CONTACT ON POS. A1; MALE CONTACT ON POS. A2
4. CAPACITANCE: 47nF ±20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 2F2CPA22S44A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: SEE NOTES	
			date	name	title:	
			drawn	13.12.13 Henneboel	D-SUB FILTER COMBINATION MALE 2W2CP SOLDER CUP	
			appd.	13.12.13 Lehmenkühler		
			norm			
		d-old		dwg no:		
a	Original			24K1A1491		
rev.	description			date	name	part no: 2F2CPA22S44A10X
				DIN-A3		
				sh: 1		