



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
4. NO CONTACTS ON POS: A1 - A2
5. CONNECTOR IS PART MARKED: 3017W2PAN99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)			
				material: SEE NOTES			
	date	name		title: D-SUB COMBINATION MALE 17W2P WIRE WRAP			
	drawn	15.05.14	Henneboel				
	appd.	15.05.14	Schmidt				
	norm			dwg no:			
d-old			13K1A4675				
rev.	a	Original			DIN-A3		
description	date	name			sh: 1		
part no:			3017W2PAN99A10X				