



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: 30µin HARD GOLD over min. 50µin NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. HIGH POWER CONTACTS 30A: COPPER ALLOY
PLATING MATING AREA: 30µin HARD GOLD over min. 50µin NICKEL
PLATING TERMINATION SIDE: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 10-12
5. CONNECTOR IS PART MARKED: 3017W5PCM43A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

tolerance	dim. in mm	
date	name	
drawn 07.04.11	Henneboel	
appd. 07.04.11	Koch	
norm		
d-old		
a Original		
rev.	description	date name



scale:	2:1	
material:	SEE NOTES	
title:	D-SUB COMBINATION MALE 17W5P SOLDER CUP	
dwg no:	13K1A3644	DIN-A3
part no:	3017W5PCM43A10X	sh: 1