



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1 - A7
5. FLOATS: COPPER ALLOY; TIN PLATED
6. CONNECTOR IS PART MARKED: 3024W7PAM99A60X CONEC ABC

RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: see notes	
	date	name		title:		
	drawn 12.07.16	Henneboel		D-SUB COMBINATION MALE 24W7P SOLDER CUP with float mount		
	appd. 12.07.16	Lehmenkühler				
	norm					
d-old			dwg no:		DIN-A3	
rev. a	Original			13K1A5253		
description	date			name	part no: 3024W7PAM99A60X	