



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: PBT GF UL 94 V-0, BLACK
3. HIGH POWER CONTACTS 30A: COPPER ALLOY
PLATING, MATING AREA: GOLD FLASH over NICKEL
PLATING, TERMINATION SIDE: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 10-12
4. CAPACITANCE: 47nF ±20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
6. CONNECTOR IS PART MARKED: 3F3SSA22S43A10X CONEC ABC

SOLDER INSTRUCTION:

1. THE WIRE HAVE TO BE PRETINNED
2. SOLDER TEMPERATURE max. 350°C
3. SOLDER TIME max. 15s

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)		
				material: SEE NOTES		
	drawn	09.04.14	Henneboel		title: C- FILTER D-SUB COMB. FEMALE 3W3SS SOLDER CUP	
	appd.	10.04.14	Lehmenkühler			
	norm					
	d-old				dwg no:	DIN-A3
a	Original			24K1A1515		
rev.	description			date	name	part no:

sh: 1